

HR-003

Enclosed Hose Reels with Polyurethane Hose

Enclosed hose reel with swivelling support Series 300 for air-water
20 Bar with hose 15 m \varnothing 8 x 12 mm

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE |
CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY |
MANUFACTURING INDUSTRY

FLUIDS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE



FEATURES	UM	VALUE
Pressure	Bar	20
Compatible fluids		Air – water 40°C
Swivel joint		Brass, swivelling hose outlet
Seals		Viton®
Characteristic		Swivelling
Material		Painted steel
Couplings		Brass
Hose		971.116
\varnothing and hose length	\varnothing – m	5/16" – 15
Inlet		G 3/8" (m)
Outlet		G 1/4" (m)
Reel flow path		Brass - Delrin®
Internal drum width	mm	124

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com

