

IP-001

Industrial pumps - s. 1200

Divorced pump s.1200, for industrial and chemical fluids, with Viton®

SECTORS

MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

FLUIDS

FRESH OIL | ANTIFREEZE | DIESEL FUEL

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)



FEATURES	UM	VALUE
Flow rate	l/min	100
Ratio		3:1
Compatible fluids		Chemical and industrial fluids
Suction tube upper body		Carbon steel
Suction tube		Carbon steel
Air inlet connection		G 1/2" (f)
Fluid outlet connection		G 1.1/2" (f)
Max supply pressure	bar	8
Max air consumption 8 bar	m ³ /min	2,8
Noise level	dB	80
Suitable for drums or tank		Modular
Packing	N° - m ³	1 - 0,20
Weight	kg	46
Dimensions (A-B-C)	cm	36 - 62,5 - 16,2

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com

