

## IP-004

### Industrial pumps - s. 1200

Flanged pump s.1200, for grease or oil with high viscosity, with suction tube for ram hoist

#### SECTORS

MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

#### FLUIDS

FRESH OIL | GREASE

#### CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)



FEATURES	UM	VALUE
Flow rate	l/min	10000 g/min
Ratio		40:1
Compatible fluids		High viscosity oils and greases
Suction tube upper body		Carbon steel
Suction tube		Carbon steel
Air inlet connection		G 1/2" (f)
Fluid outlet connection		G 1/2" (f)
Max supply pressure	bar	8
Max air consumption 8 bar	m <sup>3</sup> /min	2,8
Noise level	dB	80
Suitable for drums or tank		Ram hoist
Packing	N° - m <sup>3</sup>	1 - 0,090
Weight	kg	21
Dimensions (A-B-C)	cm	44,5 - 60 - 5,08

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

[sales@afrifuel.com](mailto:sales@afrifuel.com) | [www.afrifuel.com](http://www.afrifuel.com)



**Africa**  
fuelProjects  
(PTY) Ltd