

GP-002

Grease pumps

Grease pump s. 700, R 65:1 - 1900 g/min, with suction tube 480 mm

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

FLUIDS

GREASE



FEATURES	UM	VALUE
Flow rate	l/min	1900 g/min
Ratio		65:1
Compatible fluids		Greases, medium/high viscosity
Suction tube upper body		Aluminium
Suction tube		Carbon steel
Air inlet connection		G 1/4" (f)
Fluid outlet connection		G 3/8" (f)
Air working pressure	bar	6 ÷ 8
Average air consumption	l/min	440
Noise level	dB	81
Air max pressure	bar	8
Suitable for drums	kg	20 ÷ 30
Pump	P/N	-
Hose reels	P/N	-
Gun	P/N	-
Drum cover	P/N	-
Follower plate	P/N	-
Grease connection hose	P/N	-
Nipple	P/N	-
Drip-tray	P/N	-
Packing	N° - m ³	1 - 0,010
Weight	kg	6,1
Dimensions (A-B-C)	cm	33,5 - 48 - 3

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com



Africa
fuelProjects
(PTY) Ltd