

IP-005

Industrial pumps - s. 1200

Flanged pump s. 1200, for grease or oil with high viscosity, with PU seals and suction tube in steel for tanks

SECTORS

MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

FLUIDS

FRESH OIL | GREASE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)



FEATURES	UM	VALUE
Flow rate	l/min	4400 g/min
Ratio		75:1
Compatible fluids		High viscosity oils and greases
Suction tube upper body		Carbon steel
Suction tube		Carbon steel
Air inlet connection		G 1/2" (f)
Fluid outlet connection		G 1/2" (f)
Max supply pressure	bar	8
Max air consumption 8 bar	m ³ /min	2,8
Noise level	dB	80
Suitable for drums or tank		Tank
Packing	N° - m ³	1 - 0,045
Weight	kg	18
Dimensions (A-B-C)	cm	44,5 - 50 - 4,5

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com



Africa
fuelProjects
(PTY) Ltd