

WD-002

Professional Waste Oil Suction-Drainers

SECTORS

MINING | AUTOMOTIVE



Suitable for an engine oil change any vehicle. By using gravity and air operated drainers, using the attached adjustable bowl or suction through the probes provided. After depressurization, no ongoing compressed air is required. This allows the mechanism to work independently. Can sustain oil temperatures at 70-80 °C.

Combined Drainers							
Article No.	Unit	Standard			With Prechamber		
		RAS-43060	RAS-4300	RAS-43115	RAS-43065	RAS-43091	RAS-43116
Tank capacity	l	65			24		
Max Draining Capacity	l	52	75	97	52	75	97
Bowl Capacity	l	15	15	15	15	15	15
Pre-Chamber Capacity	l	-	-	-	8	8	8
Noise Level	dB	75	75	75	75	75	75
Air Pressure	Bar	6.5-7	6.5-7	6.5-7	6.5-7	6.5-7	6.5-7
Depressurisation Time	Min	2	2.5-3	3-3.5	2	2.5-3	3-3.5
Suction Hose	Min	1.5-2	1.5-2	1.5-2	1.5-2	1.5-2	1.5-2
Total Suction Capacity	l	43-45	60-65	85-90	43-45	60-65	85-90
Suction Hose	M	2/2	2/2	2/2	2/2	2/2	2/2
Max Draining Pressure	Bar	0.5	0.5	0.5	0.5	0.5	0.5
Probes Sets	-	RAS – 45560	RAS – 45560	RAS – 45560	RAS – 45560	RAS – 45560	RAS – 45560

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com

