

WD-004

Professional Waste Oil Suction-Drainers

SECTORS

MINING | AUTOMOTIVE



Suitable for an engine oil change any vehicle. By using gravity and air operated drainers, using the attached adjustable bowl or suction through the probes provided. After depressurization, no ongoing compressed air is required. This allows the mechanism to work independently. Can sustain oil temperatures at 70-80 °C.

Gravity Drainers

Article No.	Unit	Central Bowl			Side Bowl		
		RAS-43060	RAS-43090	RAS-43115	RAS-43066	RAS-43091	RAS-43116
Tank capacity	l	65	90	115	65	90	115
Max Draining Capacity	l	52	75	97	52	75	97
Bowl Capacity	l	15	15	15	15	15	15
Pre-Chamber Capacity	l	-	-	-	-	-	-
Noise Level	dB	-	-	-	-	-	-
Air Pressure	Bar	-	-	-	-	-	-
Depressurisation Time	Min	-	-	-	-	-	-
Suction Time	Min	-	-	-	-	-	-
Total Suction Capacity	l	-	-	-	-	-	-
Suction Hose	Min	Draining 2	Draining 2	Draining 2	Draining 2	Draining 2	Draining 2
Max Draining Pressure	Bar	0.5	0.5	0.5	0.5	0.5	0.5
Probes Sets	-	-	-	-	-	-	-