

MHR. 002

Series 500 – Manual – Painted Steel

Perfect for harsh industrial conditions. Toughness and endurance certified, there is an array of uses. Suitable for air, water, oil, grease and diesel fuel.

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE |
 CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY |
 MANUFACTURING INDUSTRY

FLUIDS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE



Hose Reel Capacity		
∅ Hose External		Length
1/4"	14mm	92m
3/8"	17mm	38m
1/2"	20mm	25m
5/8"	21mm	21m
3/4"	27mm	15m
1"	34mm	7m

Item	Painted Steel	Connection	
		Inlet	Outlet
Air - Water 20 bar - brass swivel joint - Viton® seals	Yes	F 1/2" G	F 1/2" G
Water max 130° C 100 bar - AISI 304 stainless steel swivel joint - Viton® seals	Yes	F 1/2" G	F 1/2" G
Water max 130° C 200 bar - AISI 304 stainless steel swivel joint - Viton® seals	Yes	F 3/8" G	F 1/2" G
Water max 130° C 400 bar - AISI 304 stainless steel swivel joint - Teflon® seals	Yes	F 3/8" G	F 1/2" G
Oil and similar 150 bar - galvanized steel swivel joint - polyurethane seals	Yes	F 1/2" G	F 1/2" G
Grease 600 bar - galvanized steel swivel joint - polyurethane seals	Yes	F 3/8" G	F 1/2" G
Diesel fuel 10 bar - brass swivel joint - Viton® seals	Yes	F 1/2" G	F 1/2" G
		For hoses from 5/8" and 3/4"	

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com