

CFH. 003

Fuel Flex EN 13765 Composite Fuel Hose GAPH

Recommended for the delivery and/or suction of a wide range of chemicals and solvents. Contact us for the correct choice of composite hose for your application

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE |
 CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY |
 MANUFACTURING INDUSTRY

FLUIDS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE



Fuel Flex GAPH		
Standard Series:	EN10GAPH TYPE 2	
Construction	Inner Wire Spiral	Galvanised(G)
	Outer Wire Spiral	Aluminium (A)
	Inner lining	Polypropylene (P)
	Cover	Polyester Fabric PVC-coated
Temperature Range	-20°C to 80°C	
Standard / Approval	BS EN 13765:2010 + A1:2015	
Work Safety Factor	The working pressure is based on a safety factor of 4:1	

Fuel Flex GAPH – Standard Duty						
Code	Working Pressure		Diameter	Bend radius	Weight	Maximum coil lengths
	Bar	Psi				
EN10GAPH25	10	150	1	68	1.1	11
EN10GAPH40	10	150	1 ½	105	1.4	11
EN10GAPH50	10	150	2	190	1.7	11
EN10GAPH65	10	150	2 ½	225	1.9	11
EN10GAPH80	10	150	3	290	2.4	15
EN10GAPH100	10	150	4	320	3.2	15

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

sales@afrifuel.com | www.afrifuel.com

