

D-008

Diaphragm Pumps – Entirely in Aluminium

Diaphragm pump in aluminium series AAB-2 with multi ported inlet / outlet, membranes and balls in Teflon® and seats in polyurethane

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE |
 CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT |
 CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

FLUIDS

FRESH OIL | WATER | DIESEL FUEL

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)



FEATURES	UM	VALUE
Flow rate	l/min	610
Ratio		1:1
Max pressure	Bar	8
Max cycles for minute	Cpm	147
Delivery for cycles	litres	4,150
Max suction lift	m	dry column 5 - wet column 7,5
Max size pumpable solids	mm	6.5
Max working temperature	°C	100
Noise level	dB	82
Max air consumption	m³/min	4,00
Air working pressure	bar	2 ÷ 6
Air inlet connection		G 3/4" (f)
Air outlet connection (muffler)		G 1" (f)
Fluid inlet connection		G 2.1/2" (f)
Fluid outlet connection		G 2" (f) ball
Balls for inlet		valve
Membranes		PTFE+Hytrel®
Balls		PTFE
Seats		polypropylene
Packing	N° - m³	1 - 0,12
Gross weight	kg	45

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 /4

sales@afrifuel.com | www.afrifuel.com

