

# VPR-003

## Pressure Relief / Sustaining Valve

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE |  
BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING  
INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

### FLUIDS

GAS | WATER



### TECHNICAL SPECIFICATION

Pattern & Size	Globe : 3-16"; DN80-400 Angle : 3-4"; DN80-100
End Connections	Threaded ; Flanged or Grooved
Body & Cover Material	Polyester Coated Cast or (10"; DN250 and Larger) Ductile Iron
Spring Material	Stainless Steel
Diaphragm Material	Nylon Fabric Reinforced NR with Rugged Insert
Bolts, Studs and Nuts Material	Zinc-Cobalt Plated Steel
Control Accessories	Brass
Tubing & Fittings	Reinforced Plastic and Brass
Pressure Rating	16 BAR ; 232 Psi
Operating Pressure Range	0.5– 16 BAR ; 7-232 Psi
Setting Range	1-16 BAR; 15-232 Psi

Africa Fuel Projects (PTY) Ltd

58 Charles Road, Glen Donald, Meyerton, 1961

Gauteng, South Africa

+27 (0) 87 285 2463 / 4

[sales@afrifuel.com](mailto:sales@afrifuel.com) | [www.afrifuel.com](http://www.afrifuel.com)

